SH 620 FS





This tool is made for these applications

Cable up to max. Ø 62 mm from conductor classes 1, 2 & 5 in accordance with DIN EN 60228 | VDE 0295 | IEC 60228

That is particularly

Cutting of three different conductor classes with one tool.

Cuts cables in a clean and smooth way. You are always perfectly prepared for the next processing step.

Handles even heavy jobs with ease, thanks to optimum transmission

The low weight and compact size make it easy for you to work.

These functions make cutting more convenient

The cable cutter can be easily operated with just one hand.

Tool lies comfortably in the hand thanks to soft handles with anti-slip protection.

Can be released in any cutting position in the event of incorrect operation.

Further advantages offered by our Made in Germany standard

Tool is extremely robust, minimal wear.

Blades can be easily replaced if necessary.

Manufactured from special steel, specially hardened and tempered parts - quality that lasts.

Technical Data

Cutting range	CU cable Diameter 62 mm 2 7/16" Cross-section max. 480 mm²
	AL cable Diameter 62 mm 2 7/16" Cross-section max. 480 mm²
Conductor classes	Class 1 solid conductors Class 2 stranded conductors Class 5 fine-stranded conductors
	DIN EN 60228 VDE 0295 IEC 60228
Dimensions (length x width)	approx. 297 mm x 100 mm
Weight	approx. 800 g